

Prowler

Ultra Light Tactical Mobility Asset

**PROWLER C4XME
VLSV/ITV**



Multiple Mission Configurable

Prowler is the only Light Tactical All Terrain Vehicle (LTATV) built from the ground up to provide an agile, powerful and stable multi-application platform. Prowler's purpose-driven design, uncompromising quality materials and rugged construction have made it the deployment choice of field operators worldwide.

Purpose Built for Extreme Operation

can-am



ATV Corp
division

PHOENIX
INTERNATIONAL

Prowler C4XM • TECHNICAL SPECIFICATIONS

Part Number: PWLRC4XM (Standard Platform Configuration Unless Specified As Optional)

Engine Type:	Rotax, V-Twin, SOHC, 8-Valve (4-Valve/Cylinder)
Displacement:	976 cc
Horsepower:	101 hp
Cooling:	Liquid
Fuel System:	iTC with EFI and 54mm Throttle Body, 2 Siemens VDO injectors
Power Train:	Automatic CVT, sub-transmission with H/L/N/R/P with standard engine braking
Drive System:	All wheel drive, switch selectable 2WD/4WD, shaft driven with Visco-Lok QE auto-locking front differential, locked rear differential
Construction:	High-Strength Steel ROPS (approved) , steel cargo racks front and rear , full coverage heavy duty aluminum skid plate system able to support entire weight of vehicle on a single point contact with a-arm/CV guards
Operation:	Standard automotive controls, Tri-Mode electronic power steering with sealed rack and pinion, adjustable driver seat, tilt wheel, passenger handhold/grab bar and advanced driver and passenger ergonomics
Speed:	70 mph (112.6 kph)
Front Suspension:	Double A-arms, Fox Defense Series Podium 2.0 HPG piggyback shocks with extra heavy-duty springs, adjustable preload and compression, 14" (35.6 cm) travel
Rear Suspension:	Torsional Trailing A-arms Independent rear suspension (TTA)with sway bar, Fox Defense Series Podium 2.0 HPG piggyback shocks with extra heavy-duty springs, adjustable preload and compression, 14" (35.6 cm) travel
Front Brakes:	Dual 214mm ventilated disc brakes with hydraulic twin-piston (27mm) calipers
Rear Brakes:	Dual 214mm ventilated disc brake with hydraulic single-piston (32mm) caliper
Instrumentation:	Digital multifunction display, Speedometer, tachometer, odometer, trip and hour meters, fuel, drive gear position, sport mode, ECO mode, 4x4 indicator, diagnostics, clock, hi-temp, low-battery and DC outlet (optional DC outlets available)
Electrical:	12 VDC Standard (optional 24 VDC auxiliary system)
Operator Safety:	Roll Over Protection System (ROPS) Exceeds SAE and ISO STDS, 4-point quick release single mechanical latch crew restraints SFI-16.1 certified, platform system designed to meet MIL-STD-882D (mission defined specification)
Passengers:	4 (6 with optional 2 rearward facing seats)
Litter Capacity:	2 Internally Longitudinally
Cargo Racking Capacity:	700 lbs. (317 kg) Front – 200 lbs. (90.7 kg) Rear – 500 lbs. (226.7 kg)
Rear Cargo Bed Dimensions:	36" L x 55" W x 16" H (91.4 cm x 139.7 cm x 40.6 cm)
Front Cargo Rack Dimensions:	24" L x 55" W (60.9 cm x 139.7 cm)
Payload Capacity:	1700 lbs. (771 kg) (includes passengers & kit)
Towing Capacity:	2000-2500 lbs. (909-1133 kg) terrain dependent, standard 2" receiver
Transport Lift/Tie Down:	Meets MIL-STD-209K/NATO STANAG 3548TN specifications
Winch:	WARN Provantage - 4500 lbs. (2041 kg) with remote control and synthetic cable (optional wireless remote control)
Wheels/Tires:	Cast aluminum beadlock wheels, 8 Ply tires 28 x 10 R14 (all wheels and tires same size, run-flat tires optional)
Fuel Capacity:	10 gal. (37.8 L)
Range:	160 miles (257 k)
Ground Clearance:	14" (35.5 cm)
Fording Depth:	36" (91.4 cm)
Wheel Base:	113.8" (289.1 cm)
Track Width:	54.5" (138.4 cm)
Overall Vehicle Dimensions:	L – 154" (391.1cm) W – 63" (160 cm) H – 74" (187.9 cm). (optional 60" (152.4 cm) height and width configuration)
Dry Weight:	1747 lbs. (792.4 kg)
Ignition:	Key with push button (optional keyless)
Lighting:	240W from 4-60W projectors (optional blackout switch and light arrays for I.R. mission specific)
Surface Finishes:	All working surfaces industrial powder coated
Security:	Anti-Theft Digitally Encoded Security System (D.E.S.S.)

*These specifications subject to change without notice. Prowler is built by the ATV Corp division of Phoenix International Systems, an **AS 9100/ISO 9001:2008 Certified Manufacturer** and a Service Disabled Veteran Owned Small Business. Prowler is a registered trademark of Phoenix International.



ATV Corp a division of Phoenix International Systems, Inc.
714 283-4800 • www.atvcorp.com